Summary Technical Data Sheet

DI Water

Product Name: DI Water

Synonyms: Deionized Water, Demineralized water, DM water

CAS Number: 7732-18-5

Formula: H_2O

Appearance: clear liquid

Boiling point: 100 °C

Molar mass: 18.015 g/mol

Density: 997 kg/m³

Product Specifications	
Test	**Specification**
Electrical Resistivity (MΩ·cm at 25 °C)	Min. 0.2 (Type IV)
Conductivity (µS·cm at 25 °C)	Max. 5 (Type IV)
pH	5.0 – 8.0

DI Water (Deionized water) is water that has been purified to remove ions and dissolved mineral salts.

Deionized water is used in many industries and laboratories for manufacturing and analysis.

Storage and Handling:	Keep containers tightly closed.
Packaging:	55 gal. / 208 L Drum
Transport Regulations:	Not classified as dangerous goods.

The above information, while not guaranteed, reflects our analysis and believed to be accurate. It is the end user's responsibility, prior to use of the above mentioned product to determine the suitability of the product. Aqua Bond shall not be, directly or indirectly responsible for damages of any nature whatsoever resulting from the use or reliance upon the above information.

Aqua Bond Inc. · PO Box 63635, Toronto, ON M1V 5K2·Tel. 416·754·7211·www.aquabond.ca